

GP1

WATERPROOF GAUGE SIZE STEREO



KEY FEATURES

Bluetooth **Bluetooth Audio** Easily stream your favorite tunes from your smartphone with Bluetooth Audio support. View track info including a song's name, artist, and album information right on the display.

288W POWER **288W Amplifier** Keep your system going with a 288W amplifier that powers up to 8 speakers or a combination of speakers and subwoofers.

IP65 **Multi-Environment Protection** Install anywhere with waterproof (rated IP65), UV, and salt/fog resistant protection enabling reliable performance in the toughest environmental conditions.

DSP EQ **DSP EQ** Allows common EQ settings to be applied to enhance music content, such as Pop, Classical and Rock or manually adjust bass and treble for a tailored sonic experience.

Variable Brightness Adjust the display brightness from 100% for normal operation to 30% brightness to reduce screen glare during night time operation.

Standard Gauge Size Our smallest stereo yet, designed to sit alongside standard dash gauges, but still packing a serious Aquatic AV feature set.

USB **USB** Play USB thumb drives with supported audio media and charge USB devices such as smartphones with USB charging.

AM/FM RADIO **AM/FM Radio** Listen to your favorite AM and FM radio stations. Save your favorite stations with 18 FM and 12 AM presets available. Compatible with both US and European frequencies.

AUX **AUX** Connect devices via stereo RCA cable with input gain of 2V for high performance with all devices.

2 YEAR WARRANTY **2 Year Warranty** Aquatic AV products are built to be reliable and durable. The GP1 comes with a two year warranty that can be extended with product registration.

SPECIFICATIONS

Supported Media:	Bluetooth Audio / USB / MP3 / AM/FM / AUX
Device Charging:	via rear USB cable (2.1A)
Display:	Monochrome TFT with blue backlight
Inputs:	Bluetooth, 1x USB, 1x stereo pair RCA
Outputs:	1x stereo pair RCA Pre-out (2V)
AM/FM Tuner:	18x FM pre-set & 12x AM pre-set memory. US/Euro frequencies
Power (max):	4x 45W (4 Ohms), 4x 72W (2 Ohms)
Amplifier Type:	Class A/B (2 Ohm stable)
Output Voltage:	10.5V - 14.4V DC
Current Draw:	7A (max) / <3mA (standby)
Waterproof:	Yes - IP65
UV Protection:	500hrs stable, ASTM D4329 compliant
Salt/Fog Protection:	500hrs stable, ASTM B117 compliant
Certifications:	CE, RoHS, WEE, FCC
Additional Features:	Clock display
	Stainless Steel mounting hardware

DIMENSIONS

